

DS-D5024FC Monitor



- LED backlit technology with full HD 1920 × 1080
- 24" LED backlight monitor
- Image processing: 3D comb filter, 3D De-interlace, 3D noise reduction
- Multiple interfaces: HDMI, VGA, BNC input, BNC output, audio in
- Built-in speaker
- Wide viewing angle: Horizontal 170°, Vertical 160°
- 24/7 operation

▪ Specification

Model	DS-D5024FC	
Display	Screen Size	23.6 inch
	Active Display Area	525.22 mm (H) × 297.22 mm (V)
	Resolution	1920 × 1080
	Backlight	D-LED
	Pixel Pitch	0.2715 mm (H) × 0.2715 mm (V)
	Brightness	250 cd/m ² (Typ.)
	Viewing Angle	178° (H) / 178° (V)
	Color Depth	16.7 million
	Contrast Ratio	41.667361111111113
	Response Time	5 ms
Power	Power Supply	100 to 240 VAC, 50/60 Hz
	Power Consumption	≤ 30 W
	Standby Consumption	0.5 W
Working Environment	Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
	Working Humidity	10% to 85%RH (No Condensation)
	Storage Temperature	- 20 °C to + 55 °C (-4 °F to 131 °F)
	Storage Humidity	5% to 95% RH (No Condensation)
General	Color	Black
	VESA	M4, 100 mm × 100 mm
	Product Dimensions (W × H × D)	561 mm × 338 mm × 45 mm (22.09" × 13.31" × 1.77") 561 mm × 339 mm × 218.5 mm (22.09" × 13.35" × 8.6") (with base)
	Mounting Type	Wall mounting
	Package Dimensions (W × H × D)	614 mm × 465 mm × 109 mm (24.17" × 18.3" × 4.29")
	Net Weight	5.1 kg (11.2 lb.)
	Gross Weight	6 kg (13.2 lb.)
	Packing List	Power cord × 1, VGA cable × 1, user manual × 1
Interface	Data Transmission Interface	USB 2.0 × 1, USB 3.0 × 1
	Video & Audio Input	HDMI × 1, VGA × 1, AUDIO IN × 1
	Video & Audio Output	AUDIO OUT × 1
	Network Interface	LAN × 1
	Loudspeaker	2 W × 2

▪ Available Model

DS-D5024FC

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq